

Table 1: Technical data

Max. Pressure	Standard Rotation	Stroke Adjustment Screw	Ø Chamber (in)	Air volume (in³)		Approx. Stroking time (sec.) ¹⁾				Operating temperature range (°F) ²⁾		
						Double acting		Spring return				
116 Psi	0° - 90°	For 1° adj. 1/4 Turn needed	6,3	opening	closing	opening	closing	opening	closing	ST	HT	LLT2
				192	300	1.5	1.7	1.8	2.1	-40 to +176	+5 to +302	-76 to +176

¹⁾ The values refer to specific test conditions; please contact AIR TORQUE for detailed information.


²⁾ Every temperature range option requires proper components and lubricant. please contact AIR TORQUE for detailed information.

Table 2: Nominal output torque for Double acting actuators (Lb-In)

Pressure	40 Psi		50 Psi		60 Psi		70 Psi		80 Psi		90 Psi		100 Psi		110 Psi		116 Psi		Approx. weight (lb)
	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	
D	2770		3462		4155		4847		5540		6232		6925		7617		8032		43,20

Table 3: Nominal output torque for Single acting actuators (Lb-In)

Pressure	40 Psi		50 Psi		60 Psi		70 Psi		80 Psi		90 Psi		100 Psi		110 Psi		116 Psi		Spring Stroke		Approx. weight (lb)
Spring Set	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	0°	90°	90°	0°	
S 05	1777	1300	2469	1992	3162	2685	3854	3377	4547	4070	5239	4762	5931	5455					1470	993	47,40
S 06	1578	1006	2271	1698	2963	2391	3655	3083	4348	3776	5040	4468	5733	5161	6425	5853			1764	1192	
S 07	1380	712	2072	1404	2764	2097	3457	2789	4149	3482	4842	4174	5534	4867	6227	5559	6642	5975	2058	1390	49,00
S 08			1873	1110	2566	1803	3258	2495	3951	3188	4643	3880	5336	4573	6028	5265	6444	5681	2352	1589	
S 09					2367	1509	3060	2201	3752	2894	4445	3586	5137	4279	5829	4971	6245	5387	2646	1788	50,50
S 10							2861	1907	3553	2600	4246	3292	4938	3985	5631	4677	6046	5093	2940	1986	
S 11									3355	2306	4047	2998	4740	3691	5432	4383	5848	4799	3234	2185	52,00
S 12													4541	3397	5234	4089	5649	4505	3528	2383	



T PTU-I EN

Power Technology Upgrade series

Pneumatic rack and pinion actuators
PT045 U → PT1000 U models

Application

Rotary pneumatic actuators for automation (on/off or modulating duties) of industrial valves such as ball valves, butterfly valves and plug valves as used in process industries like chemical, petrolchemical, pharmaceutical, water treatment, oil & gas.

The Power Technology Upgrade series actuators are available in two configurations: double acting and single acting.

Mechanical Spring Return is for fail-safe applications and can be supplied for "Fail Close" or "Fail Open" safety function.

Double acting actuators can be used for a "Fail Last" Position safety function.

Special features

- Alodur hard anodized extruded aluminum body for corrosion protection, low friction and wearing resistance
- Dual piston rack and pinion design for compact construction and symmetric mounting.
- Fully machined teeth on piston racks and pinion shaft for accurate positioning, low backlash and maximum engagement.
- Two independent external travel stop adjustments.
- Universal and anti-blowout drive shaft with multiple valve connection options.
- Identical body and end caps for double acting and spring return configuration to allow field conversion.
- Stainless steel fasteners for high corrosion resistance.
- Multiple bearings and guides for high cycles and low friction
- Modular preloaded springs.
- Extended working temperature range as standard.

Versions

- Spring return:
 - 90°, 120°, 135° and 180° rotation.
- Double acting:
 - 90°, 120°, 135° and 180° rotation,




Fig. 1: Power Technology Upgrade series actuator

Further versions

- Actuator with extra travel stop limitations (R100; R50; RC100),
- Fast acting,
- Low working temperature LLT2,
- High working temperature HT,
- Special painting according to ISO 12944,
- Water operated actuator,
- Natural gas operated actuator.

Complementary parts

- Lock out system on adjustment screws,
- Block and safety lock-out system,
- Gearbox.

Principle of operation

1. DOUBLE ACTING

Refer to Fig. 2.

In case of the double acting configuration air pressure is necessary for both strokes (A and B).

2. SINGLE ACTING

Refer to Fig. 3.

When air pressure is supplied through port "2" (A') into the actuator body, the linear force applied on the piston surface generates the pinion rotation, driving the valve to a defined position. At the same time the actuator springs are compressed.

When air pressure is discharged (B'), the springs are automatically released, driving the rack and pistons back to the original position and thus the valve to the fail-safe position.

Direction of action and stroke adjustment

The standard rotating direction for the PTU Series actuators is clockwise to close.

Standard PTU Series actuators are designed for 90° rotating angle, with travel stop allowing adjustment for -5° up to +15° on the close position and for +5° up to -15° on the open position as per Fig. 4. For PT045 U stroke adjustment is only available on request.

For spring return actuator in case of pressure, power or signal failure the springs drive the actuator in the fail position that can be FAIL OPEN or FAIL CLOSE.

Power operating media

Use dry or lubricated air or inert gas.

- Make sure the operating media is compatible with the actuator internal parts and lubricant.
- In case of pressure medium different than Group 2 fluids according to the PED 2014/68/EU, contact AIR TORQUE.
- The operating media must have a dew point equal to 20°C (-4°F) or at least 10°C (18°F) below the ambient temperature.
- The maximum particle size contained into the operating media must not exceed 30 µm.

Further information

The actuators can be operated in different ways:

- direct mounting of control devices (for example a solenoid valve or a manifold) with NAMUR interface,
- threaded connections (to pressurize port "2" and "4") with air lines from separate electro-pneumatic control system.




Fig. 2: Double acting operation




Fig. 3: Single acting operation




Fig. 4: Stroke adjustment range

Installation

Refer to the EB AT-RP-PTU mounting and operating instructions.

Ordering text

Refer to the Catalogue PTU-E-XX for actuators available options and ordering codes.

Further versions

- **Extra travel stop limitations (R100/R50/RC100)**

R50/R100

Actuator travel stop limitations are available in both opening or closing directions for standard assembly (clockwise to close) in order to provide maximum flexibility.

the R50 and R100 allows to limit the actuator stroke in opening direction (from 90° to 0°).

The R50 allow to limit the 45% of the stroke (from 90° to 45° stroke range).


The R100 allow to limit the 100% of the stroke (from 90° to 0° stroke range).

both R50 and R100 extra travel stop adjustments are equipped with protective plugs at the two adjustment screws ends in order to protect the two ends and to avoid potential cut due to screws sharp edges.

The R50 and R100 can be directly supplied mounted on the actuators or supplied as kits to retrofit sold actuators.

RC100

The RC100 allows to limit the 100% of the stroke in closing direction (from 90° to 0° stroke range).



TYPICAL APPLICATION: any application where an extra travel stop opening or closing position is required.

- **Fast acting**

The Fast Acting (FA) actuators are special actuators able to stroke faster respect the standard actuators. They are available both in double acting and in spring return configurations.

This type of actuators has enlarged ports and internal canalization which allows an higher flow rate of the the actuator and so a quicker operation in closing and/or opening direction.

TYPICAL APPLICATION: any application where actuator quick action is required

- **Low and high working temperature configurations**

In case minimum working temperature up to -60°C or maximum working temperature up to +150°C are required, the following special product configuration are available:

- LLT2 version for extreme low operating temperature range:
-60° C (-76° F) → +80° C (+176° F);
LLT2 version actuators have stainless steel drive shaft.
Aluminium drive shaft actuator version (LLT2A) can be

supplied on request in order to achieve a more competitive price.

LLT2 and LLT2A version actuators have the same technical features except for the drive shaft material and extra bushings for LLT2A.

- HT version for high operating temperature range:
- 15° C (+5° F) → +150° C (+302° F).

TYPICAL APPLICATION: where the required working temperature exceeds the actuator standard working temperature range (-40°C / +80°C)

- **Special painting according to ISO 12944-2**

Different protection levels available in order to meet the field corrosion resistance requirements.

the protection levels are different combination of materials and painting cycles/types.

According to the ISO 12944-2 the standard available protection levels with single layer painting go approx. from the C3 level up to C5 level.

Special paint systems are available according to customer specification, including multilayer painting.

- **Water operated actuator**

Standard PTU actuators are operated with dry air or inert gas. Special actuator configurations are available to operate with water as supply media.

Contact Air Torque for further detailed information.

- **Natural gas operated actuator**

Standard PTU actuators are operated with dry aie or inert gas. Special actuator configurations are available to operate with natural gas (sweet and dry or sour) as supply media.

Contact Air Torque for further detailed information.

Complementary parts

- **Actuator with lock out system on adjustment screws**

In order to permanently lock the actuator in position, the actuator can be supplied with a special locking device by using a padlock and therefore preventing unwanted operation.

The lock out system on adjustment screws can be directly supplied mounted on the actuators or supplied as kits to retrofit sold actuators.



Fig. 24: Actuator with lock out system on adjustment screws

- **Actuator with block and safety lock-out system**

The block and safety lock-out system permits to lock the actuator and the valve in specific cases, despite the fail action of the actuator.




Fig. 23: Actuator with Block and safety lock-out system

- **Actuator with declutchable gearbox**

It is a manual override system designed to provide manual operation to stroke the actuator and the valve. The gearbox can have a vital role to stroke the actuator and the valve in the safe position when the supply pressure is not available in case of any emergency situation. The actuator and the valve are operated rotating a handwheel.

AIR TORQUE can provide the actuator packed with the declutchable gear box (buyout item).

The gearbox valve interface and connection (ISO flange and/or valve stem adaption) are defined in the purchase order.




Fig. 22: Actuator with gearbox